

Trade name: einzA Härter für Lawirostal**Product no.:** 0171237**Current version :** 4.0.1, issued: 14.03.2023**Replaced version:** 4.0.0, issued: 25.11.2021**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name

einzA Härter für Lawirostal**1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**

einzA Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Eye Dam. 1; H318

Flam. Liq. 3; H226

Skin Irrit. 2; H315

STOT RE 2; H373

STOT SE 3; H335

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS05



GHS07



GHS08

Signal word

Danger

Hazardous component(s) to be indicated on label:

Reaction mass of xylene and ethylbenzene

butan-1-ol

Trade name: einZA Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Hazard statement(s)

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure

Hazard statements (EU)

EUH208	Contains Amines, polyethylenepoly-, triethylenetetramine fraction. May produce an allergic reaction.
--------	--

Precautionary statement(s)

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P370+P378	In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	Reaction mass of xylene and ethylbenzene		
	- 905-588-0 - 01-2119488216-32	Acute Tox. 4; H312 Acute Tox. 4; H332 Asp. Tox. 1; H304 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT RE 2; H373 STOT SE 3; H335	>= 25.00 - < 50.00 wt%
2	butan-1-ol		
	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Acute Tox. 4; H302 Eye Dam. 1; H318 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335 STOT SE 3; H336	>= 5.00 - < 10.00 wt%
3	Amines, polyethylenepoly-, triethylenetetramine fraction		

Trade name: einZA Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

90640-67-8 292-588-2 - 01-2119487919-13	Acute Tox. 4; H302 Acute Tox. 4; H312 Aquatic Chronic 3; H412 Eye Dam. 1; H318 Skin Corr. 1B; H314 Skin Sens. 1; H317	< 2.50	wt%
--	--	--------	-----

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	STOT RE 2; H373: C >= 10%	-	-

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

Trade name: einZA Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
List of approved workplace exposure limits (WELs) / EH40			
Butan-1-ol			
	WEL short-term (15 min reference period)	154	mg/m ³ 50 ppm
	Comments	Sk	

DNEL, DMEL and PNEC values

Trade name: einza Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Reaction mass of xylene and ethylbenzene			-	
				905-588-0	
	dermal	Long term (chronic)	systemic	212.00	mg/kg/day
	inhalative	Short term (acute)	systemic	442.00	mg/m ³
	inhalative	Short term (acute)	local	442.00	mg/m ³
	inhalative	Long term (chronic)	systemic	221.00	mg/m ³
2	butan-1-ol			71-36-3	
				200-751-6	
	inhalative	Long term (chronic)	local	310	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Reaction mass of xylene and ethylbenzene			-	
				905-588-0	
	oral	Long term (chronic)	systemic	12.50	mg/kg/day
	dermal	Long term (chronic)	systemic	125.00	mg/kg/day
	inhalative	Short term (acute)	systemic	260.00	mg/m ³
	inhalative	Long term (chronic)	systemic	65.30	mg/m ³
	inhalative	Short term (acute)	local	260.00	mg/m ³
	inhalative	Long term (chronic)	local	65.30	mg/m ³
2	butan-1-ol			71-36-3	
				200-751-6	
	oral	Long term (chronic)	systemic	1.562	mg/kg/day
	dermal	Long term (chronic)	systemic	3.125	mg/kg/day
	inhalative	Long term (chronic)	systemic	55.357	mg/m ³
inhalative	Long term (chronic)	local	155	mg/m ³	

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	Reaction mass of xylene and ethylbenzene		-	
			905-588-0	
	water	fresh water	0.327	mg/L
	water	marine water	0.327	mg/L
	water	fresh water sediment	12.46	mg/kg
	water	marine water sediment	12.46	mg/kg
	soil	-	2.31	mg/kg
	sewage treatment plant	-	6.58	mg/L
2	butan-1-ol		71-36-3	
			200-751-6	
	water	fresh water	0.082	mg/L
	water	marine water	0.008	mg/L
	water	Aqua intermittent	2.25	mg/L
	water	fresh water sediment	0.324	mg/kg dry weight
	water	marine water sediment	0.032	mg/kg dry weight
	soil	-	0.017	mg/kg dry weight
sewage treatment plant	-	2476	mg/L	

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Trade name: einza Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Filter A2P2 (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term contact / splash protection: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	120	min
Appropriate Material	In case of prolonged exposure: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	480	min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form	
liquid	
Colour	
according to product name	
Odour	
like solvents	
pH value	
No data available	
Boiling point / boiling range	
Value	> 120 °C
Reference substance	solvent mixture
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Value	24 - 26 °C
Method	closed cup
Ignition temperature	
Value	> 200 °C
Reference substance	solvent mixture

Trade name: einZA Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
Value	>	0.6	% vol
Reference substance	solvent mixture		
Upper explosion limit			
Value	<	7.5	% vol
Reference substance	solvent mixture		
Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C
Reference substance	solvent mixture		
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	0.93	-	0.93 g/cm ³
Reference temperature		20	°C
Method	DIN 51757		
Solubility in water			
Comments	immiscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No data available			
Kinematic viscosity			
Value	110	-	120 sec
Reference temperature		20	°C
Method	DIN EN 2431 (4 mm)		
Solvent separation test			
Value	<	3	%
Reference temperature		20	°C
Particle characteristics			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Trade name: einza Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einza Härter für Lawirostal
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

Acute oral toxicity	
No data available	

Acute dermal toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einza Härter für Lawirostal
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
LD50	appr.	3430	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einza Härter für Lawirostal
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists)).

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
LC50	>	17.76	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
Species	rabbit		

Trade name: einZA Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Source Evaluation	ECHA irritant
----------------------	------------------

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		strongly irritant	

Respiratory or skin sensitisation	
No data available	

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Carcinogenicity	
No data available	

STOT - single exposure	
No data available	

STOT - repeated exposure	
No data available	

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure	
<p>Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the mixture and exposure to spray mist and vapour should be avoided.</p>	

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
LC50		1376	mg/l
Duration of exposure		96	h

Trade name: einzA Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Species	Pimephales promelas
Method	OECD 203
Source	ECHA

Toxicity to fish (chronic)	
No data available	

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
EC50		1328	mg/l
Duration of exposure		48	h
Species		Daphnia magna	
Method		OECD 202	
Source		ECHA	

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
NOEC		4.1	mg/l
Duration of exposure		21	day(s)
Species		Daphnia magna	
Method		OECD 211	
Source		ECHA	

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
EC50		225	mg/l
Duration of exposure		72	h
Species		Pseudokirchneriella subcapitata	
Method		OECD 201	
Source		ECHA	

Toxicity to algae (chronic)	
No data available	

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
EC50		4390	mg/l
Duration of exposure		17	h
Species		Pseudomonas putida	
Method		DIN 38412	
Source		ECHA	

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
Type		DOC decrease	
Value		92	%
Duration		20	day(s)
Method		OECD	
Source		ECHA	
Evaluation		readily biodegradable	

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Trade name: einZA Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	butan-1-ol	71-36-3	200-751-6	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: P5c

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 34.81 %

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Trade name: einZA Härter für Lawirostal

Product no.: 0171237

Current version : 4.0.1, issued: 14.03.2023

Replaced version: 4.0.0, issued: 25.11.2021

Region: GB

H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 653623